

Kel-Prime Specifications & Applications

Note: Kel-Prime is a multi-functional product that is highly concentrated for a number of applications.

A. Mixing one gallon of Kel-Prime with one gallon of clean tap water will cover 800 square feet of area and will provide a bonding surface for the following applications:

1. Finish stucco plaster over:

- a. brown coat plaster
- b. one coat plaster
- c. CMU block, concrete, brick, etc.
- d. gypsum board
- e. vinyl
- f. glass
- g. steel

2. Curing, hardening and waterproofing over:

- a. finish coat plaster
- b. one coat plaster
- c. concrete
- d. shotcrete
- e. rockscapes
- f. waterscapes
- g. block

Paint primer over:

- a. gypsum
- b. block
- c. concrete
- d. steel
- e. wood
- f. plaster
- g. shotcrete
- h. etc.

3. Paint additive to create elastomeric paint. Add **8 ozs. per one gallon** of latex paint. **Box paint five times.**

4. Application using sprayer, brush, roller, etc:

Apply one good coat only. **Do not overlap** after the first application has dried.

5. Cleanup: Clean with water after using all equipment, brushes, rollers, etc. **This is important.**

6. Do not allow Kel-Prime to dry on any surface that you do not want the application on.

7. Kel-Prime is shipped on 4 one-gallon containers. This will weigh forty pounds and the box measures 12"x12". It also comes in 55-gallon drums weighing 538 pounds.
8. For service call (800)845-1833.

End of Section.