

Kel-Crete Industries, Inc.

General Partner of CJG LP

Phone: 918-744-0800, 800-845-1833

PO Box 52217
Tulsa, OK 74152-0217

Fax: 918-744-0885
E-Mail: kelcrete@sbcglobal.net
WWW: Kel-Crete.com

Technical Data Sheet

(N/A= Non-Applicable, N/D=Not Determined)

Kel-Crete Premium Liquid Admixture

Section 1 – Chemical Product and Company Identification

Brand name: Kel-Crete Premium Liquid Admixture Contact: Kel-Crete Industries, Inc.
Chemical formula: sodium resinate PO Box 52217
Chemical family: wood resin Tulsa, OK 74152-0217
Synonyms: See material safety data sheet Emergency phone numbers:
Formula: N/A Kel-Crete Ind., Inc. 800-845-1833,
Molecular weight: N/A 918-744-0800
Inventory No: KCOL 71703-2

Section 2 – Physical Data

Boiling point: 212 degrees F. Specific gravity (H2O=1): 1.08
Vapor pressure: N/D Appearance and odor: brown liquid, resin odor
Vapor: Density (Air=1): greater 1 Evaporation rate: (Butyl acetate=1) N/D
Ph: approx. 12

Section 3 – Storage Method

Storage: Always store product sealed in cool/dry climatic conditions when not in use.

Stacking: Never stack product over three boxes high.

Freezing: Avoid freezing

Reference: Refer to Material Safety Data Sheet (MSDS)

Section 4 – Packaging and Handling

Four (4) one-gallon containers per box, or 55-gallon drums. Palletized 27 boxes per pallet and stretch wrapped weighing approximately 40 lbs. per box or 1,080 lbs. per pallet. Drums are approximately 460 lbs. Product has a Class 50 Dept. of Transportation rating (non-toxic, non-hazardous). Information concerning the handling and use of this product is provided in a Material Safety Data Sheet (MSDS). This MSDS must be fully read and understood prior to any exposure prior to any exposure, handling, or use of this product.

Section 5 – Application

Plaster mortar: 2 to 3 ozs. per 94 lbs. cement Stucco mortar: 2 to 3 ozs. per 94 lbs. cement
Masonry mortar: 2 to 3 ozs. per 94 lbs. cement Shotcrete mortar: 3 ozs. per 7 sacks cement per cu. yd.
Grout mortar: 3 ozs. per 7 sacks cement per cu. yd. Mix.
Mix. Concrete: 2 ½ ozs. per cu. yd. Mix.

Other uses: waterscapes, rockscapes, zoos, etc.

Functions: water reducer, plasticizer, air entraining, gelling.

Special mix design mortars: Call for technical support at 800-845-1833.

Information presented herein has been compiled from sources regarded as dependable, accurate and reliable to the best of our knowledge and belief, but it is not suggested to be so. Nothing herein is to be construed as recommending any practice or any product violation of any law or regulation. It is the user's responsibility to determine the suitability of any materials for a specific purpose and adopt necessary safety precautions. We make no warranty as to results to be obtained in using any material, and since conditions or use are not under our control we must necessarily disclaim all liability with respect to use of any material supplied by us.